



(slika je simbolična)

Servisna enota VARNOSTNA »FUTURA«, Velikost 4, G 1

Kategorija: [SAFETY service unit set](#)
Šifra: **100272RIE**

Kratek opis

Service station SAFETY »FUTURA«, Ball valve - start-up valve - 2-part service unit, Size 4, G 1, Input pressure 2.5 - 16 bar. These compressed air service unit sets, comprising a ball valve with silencer, a start-up valve and one out of a pressure regulator, filter regulator or service unit, meet even the strictest requirements for operating reliability and accident prevention!

Tehnične Specifikacije

Min. temperaturno območje [°C]	-10
Element filtra	Cellpor (PE)
Membrane	NBR
	At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar
Merjenje pretoka	G 1
Navoj	Fully-automatic
Odtok kondenzata	Silencer (ball valve)
Odžračevalni vtič	PA66 GF60
Ohišje	Yes
Poraba zraka	Material: Die-cast zinc
Priključni navoj	FUTURA
Serijska	Compressed air, neutral gases
Srednje	NBR
Tesnilo	1.5 l/min (depending on secondary pressure)
Max. notranja poraba zraka	2.5
Min. krmilno območje [bar]	2.5
Min. vhodni tlak [bar]	2.5
Velikost	4
Rang filtra [µm]	5
Max. krmilno območje [bar]	8
Zaslon manometra max. [bar]	10
Max. vhodni tlak [bar]	16
Max. temperaturno območje [°C]	50
C [mm]	137.0
A [mm]	340.0
B [mm]	343.0
Pretok [l/min]	10000