



(slika je simbolična)

## stand. cilinderdelujoč v dveh smerehbat Ø 63hod 100G 3/8

Kategorija: [Metalwork](#)  
Šifra: **106220RIE**

### Kratek opis

Standard cylinder, ISO 15552, double-acting, Piston Ø 63, Stroke 100, G 3/8, Working pressure max. 10 bar, Temp. -10 °C to 80 °C

These cylinders are ideal for a wide range of applications owing to their robust design and excellent value for money. The standard type has a double-acting cylinder and features a magnetic piston as well as integrated cushioning.

The magnetic switches can be mounted in two T-slots on the same side as the compressed air supply.

The version with a 125 mm bore is provided with fixing accessories on three sides as standard.

Suitable for filtered, unlubricated or lubricated compressed air.

If lubrication is used, it must be continuous.

### Tehnične Specifikacije

|                                |                                                   |
|--------------------------------|---------------------------------------------------|
| Min. temperaturno območje [°C] | -10                                               |
| Bat                            | POM                                               |
| Batnica                        | C45 steel, hard chrome-plated                     |
| Cushioning                     | cushioned                                         |
| ET batnice                     | M16x1.5                                           |
| Ffunkcija                      | double-acting                                     |
| Gewinde Kolbenstange           | male piston rod                                   |
| Magnet                         | with magnet                                       |
| Navoj na batnici               | M16x1.5                                           |
| Oblika                         | Heads / jacket with self-tapping screws           |
| Ovoj                           | Anodised aluminium jacket with integrated T-slots |
| Povezava                       | G 3/8                                             |
| Standard                       | acc. to ISO 15552                                 |
| Tesnilo                        | NBR                                               |
| Min. nastavljeni tlak [bar]    | 0.3                                               |
| Max. delovni tlak [bar]        | 10                                                |
| Batnica Ø [mm]                 | 20                                                |
| Bat Ø [mm]                     | 63                                                |
| Max. temperaturno območje [°C] | 80                                                |
| Stroke [mm]                    | 100                                               |