



## Throttle valve, both directions throttling (B) push-in connector, M5

Kategorija: [Bidirectional flow control valves](#)  
Šifra: **106980RIE**

(slika je simbolična)

### Kratek opis

Throttle valve, both directions throttling (B) push-in connector hose 6, M5, PN max. 10 bar, Temperature -20 °C to 80 °C  
For throttling flow rates and regulating the piston speed of cylinders. Small dimensions, ideal for tight spaces. To be screwed directly into the valve or cylinder. The set flow rate can be locked via the lock nut in the version with knurled screw. The variants in banjo bolt construction can be rotated during assembly and are fixed after tightening. The variants with plug-in connector, rotated can also be rotated freely after assembly. The seals and lubricants used are silicone-free.

### Tehnične Specifikacije

|                                |                                                                           |
|--------------------------------|---------------------------------------------------------------------------|
| Min. temperaturno območje [°C] | -20                                                                       |
| Design                         | Banjo bolt construction                                                   |
| Ffunkcija                      | Both directions throttling (B)                                            |
| Navoj                          | M5                                                                        |
| Silicone-free                  | Yes                                                                       |
| Telo                           | Nickel-plated brass                                                       |
| Tesnilo                        | NBR                                                                       |
| Vrsta povezave                 | Plug-in connector                                                         |
| Zarobljena tesnila             | Polyamide, glass fibre-reinforced (only parts in banjo bolt construction) |
| Za cevi [mm]                   | 6                                                                         |
| a/f [mm]                       | 8                                                                         |
| Max. obratovalni tlak [bar]    | 10                                                                        |
| C [mm]                         | 21.7                                                                      |
| B [mm]                         | 24.5                                                                      |
| Max. temperaturno območje [°C] | 80                                                                        |