



(slika je simbolična)

Tlačni reg. s pnevmatskim dalj. upravljanjem »multifix« G 1

Kategorija: [Pressure regulators pneumatic remote controlled](#)
Šifra: **133106RIE**

Kratek opis

Pressure regulator pneumatic remote controlled »multifix«, without pressure gauge, Size 4, G 1, Input pressure max. 16 bar

Diaphragm pressure regulator, self-relieving, with pneumatic remote control. The pressure is set with a pilot pressure regulator (1:1 ratio). The output pressure corresponds to the set pressure of the pilot pressure regulator. Either a standard or a precision pressure regulator can be used to regulate the pilot pressure.

Tehnične Specifikacije

Merjenje pretoka	At $P_1 = 10$ bar, $P_2 = 6,3$ bar and pressure drop $\Delta p = 1$ bar
Navoj	G 1
Ohišje	Die-cast aluminium
Povezava vodenega zračnega tlaka	G 1/4
Serijska	multifix
Tesnilo	NBR
Velikost	4
Max. vhodni tlak [bar]	16
DN	25
D [mm]	53.0
Max. sobna temperatura [°C]	60
Max. temperatura medija [°C]	60
A [mm]	85.0
C [mm]	88.0
B [mm]	141.0
Pretok [l/min]	12000