



(slika je simbolična)

## Tlačni regulator iz nerjavečega jekla, 1.4401, G 1, 0.4 - 4.0 bar

Kategorija: [Stainless steel pressure regulators 1.4401](#)  
Šifra: **133533RIE**

### Kratek opis

Stainless steel pressure regulator, 1.4401, with secondary venting (reversible), Size 4, G 1, Control range 0.4 - 4.0 bar  
Stainless steel regulators for use in the chemical industry, mining, plant construction and special machinery industries, pneumatics, etc.  
Pressure setting by hexagon head screw.

### Tehnične Specifikacije

|                              |                                                                          |
|------------------------------|--------------------------------------------------------------------------|
| Membrane                     | NBR/PTFE                                                                 |
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6$ bar and pressure drop $\Delta p \leq 1$ bar |
| Navoj                        | G 1                                                                      |
| Ohišje                       | Stainless steel 1.4401 (AISI 316)                                        |
| Tesnilo                      | NBR                                                                      |
| Min. krmilno območje [bar]   | 0.4                                                                      |
| Max. krmilno območje [bar]   | 4                                                                        |
| Velikost                     | 4                                                                        |
| Max. vhodni tlak [bar]       | 30                                                                       |
| Max. sobna temperatura [°C]  | 80                                                                       |
| Max. temperatura medija [°C] | 80                                                                       |
| C [mm]                       | 100.0                                                                    |
| A [mm]                       | 120.0                                                                    |
| D [mm]                       | 136.0                                                                    |
| B [mm]                       | 236.0                                                                    |
| Pretok [l/min]               | 10195                                                                    |