



(slika je simbolična)

## Tlačni regulator »multifix«, Velikost 4, G 3/4, 0.5 - 10 bar

Kategorija: [Pressure regulators](#)Šifra: **133099RIE**

### Kratek opis

Pressure regulator »multifix«, incl. pressure gauge, Size 4, G 3/4, Input pressure max. 16 bar, Control range 0.5 - 10 bar Reversible diaphragm pressure regulators, independent of inlet pressure, with self-relieving design. The pressure setting can be locked by pushing the button down.

### Tehnične Specifikacije

|                              |                                                                         |
|------------------------------|-------------------------------------------------------------------------|
| Merjenje pretoka             | At $P_1 = 10$ bar, $P_2 = 6.3$ bar and pressure drop $\Delta p = 1$ bar |
| Navoj                        | G 3/4                                                                   |
| Ohišje                       | Die-cast aluminium                                                      |
| Poraba zraka                 | Yes                                                                     |
| Serijska                     | multifix                                                                |
| Tesnilo                      | NBR                                                                     |
| Vzmet pokrova motorja        | POM-brass                                                               |
| Min. krmilno območje [bar]   | 0.5                                                                     |
| Max. notranja poraba zraka   | 1,5 l/min (depending on secondary pressure)                             |
| Velikost                     | 4                                                                       |
| Max. krmilno območje [bar]   | 10                                                                      |
| Max. vhodni tlak [bar]       | 16                                                                      |
| Zaslon manometra max. [bar]  | 16                                                                      |
| DN                           | 20                                                                      |
| D [mm]                       | 53.0                                                                    |
| Max. sobna temperatura [°C]  | 60                                                                      |
| Max. temperatura medija [°C] | 60                                                                      |
| A [mm]                       | 85.0                                                                    |
| C [mm]                       | 125.0                                                                   |
| B [mm]                       | 178.0                                                                   |
| Pretok [l/min]               | 12000                                                                   |