

Datum: 27.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Varnostni krogelni ventil, z zaklepom, brez izpustom, Rp 2

Kategorija: [Safety ball valves, lockable, without relief port](#)  
Šifra: **103148RIE**

### Kratek opis

Safety ball valve, lockable, without venting hole, nickel-plated brass, Operating temp. max. 170°C, Rp 2, DN 50, PN max. 40 bar  
2/2-way safety ball valves made of nickel-plated brass.  
The ball valve can be locked manually.  
Full bore, heavy-duty type.

### Tehnične Specifikacije

|                               |                            |
|-------------------------------|----------------------------|
| Min. delovna temperatura [°C] | -40                        |
| Bore diameter padlock         | ca. 7.4 mm                 |
| Krogelno tesnilo              | PTFE                       |
| Material                      | Nickel-plated brass        |
| Material navojev              | Nickel-plated brass        |
| Navoj                         | Rp 2                       |
| Ročica                        | Steel - PVC coated         |
| Standardni navoj              | Rp thread acc. to EN 10226 |
| Stebelno tesnilo              | PTFE                       |
| PN [bar]                      | 40                         |
| DN                            | 50                         |
| B [mm]                        | 92.0                       |
| L [mm]                        | 135.0                      |
| A [mm]                        | 158.0                      |
| Max. delovna temperatura [°C] | 170                        |