

Datum: 27.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



## Varnostni krogelni ventil, z zaklepom, z izpustom, Rp 3/4

Kategorija: [Safety ball valves, lockable, with relief port](#)  
Šifra: **103152RIE**

(slika je simbolična)

### Kratek opis

Safety ball valve, lockable, Venting hole M5, nickel-plated brass, Operating temp. -10 °C to 100 °C, Rp 3/4, DN 20, PN max. 14 bar  
Safety ball valves, two parts, made of nickel-plated brass. Specially designed for pneumatic applications.  
The valve shuts off the supply line and bleds the application area.  
Lockable hand lever in closed position ensures a high protection against manipulation.

### Tehnične Specifikacije

|                               |                            |
|-------------------------------|----------------------------|
| Min. delovna temperatura [°C] | -10                        |
| Bore diameter padlock         | ca. 7.3 mm                 |
| Izpušni vtič                  | M5                         |
| Krogelno tesnilo              | PTFE                       |
| Krogla                        | Chrome-plated brass        |
| Material navojev              | Nickel-plated brass        |
| Navoj                         | Rp 3/4                     |
| Ohišje                        | Nickel-plated brass        |
| Ročica                        | Steel - PVC coated         |
| Standardni navoj              | Rp thread acc. to EN 10226 |
| Stebelno tesnilo              | FKM                        |
| Max. obratovalni tlak [bar]   | 14                         |
| DN                            | 20                         |
| B [mm]                        | 60.0                       |
| L [mm]                        | 64.0                       |
| Max. delovna temperatura [°C] | 100                        |
| A [mm]                        | 117.0                      |