

Datum: 23.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Vtični-L fitting Metallice vrt., M5 o., Cev zunanja Ø 6

Kategorija: [Male elbow, swivel type, parallel ET with O-ring](#)
Šifra: **108895RIE**

Kratek opis

Push-in L-fitting »metallica«, rotating, M5 o., for hose exterior Ø 6 mm, Working pressure -0.98 to 16 bar, nickel-plated brass

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

Tehnične Specifikacije

Min. delovna temperatura [°C]	-20
Min. delovni tlak [bar]	-0.98
Material	Nickel-plated brass
Navoj	M5
Priporočena cev	PA and PU
Rokav	Nickel-plated brass
Serijska	metallica
Vpenjalni obroč	Male elbow, swivel type, parallel male thread with O-ring (FPM)
Za cevi O.D. [mm]	6
a/f [mm]	9
L2 [mm]	14.5
Max. delovni tlak [bar]	16
L1 [mm]	21.0
Max. delovna temperatura [°C]	150