

Datum: 26.05.2024

**Davčna št.:** SI 56119488  
**Telefon:** 01 500 14 42  
**E-mail:** [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
**WWW:** [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Vtični L nast.-prik. Click-klak zunanja Ø 5 mm

Kategorija: [Union elbows - click-clock](#)  
Šifra: **108754RIE**

### Kratek opis

Push-in L-connector »click-clock« for hose exterior Ø 5,  
Working pressure -0.99 to 16 bar, Operating temperature  
-20 °C to 80 °C

The advanced version of our highly successful push-in  
fittings series manufactured in nickel-plated brass.

Advantages of this new, optimised series:

- Much easier connection and disconnection of the hose, even with repeated mounting
- Can also be used for non-calibrated hoses
- Suitable for vacuum operation

### Tehnične Specifikacije

|                               |                     |
|-------------------------------|---------------------|
| Min. delovna temperatura [°C] | -20                 |
| Min. delovni tlak [bar]       | -0.99               |
| Material                      | Nickel-plated brass |
| Priporočena cev               | PA, PU              |
| Rokav                         | Hostaform           |
| Serijska                      | click-clock         |
| Vpenjalni obroč               | Stainless steel     |
| Za cevi O.D. [mm]             | 5                   |
| Max. delovni tlak [bar]       | 16                  |
| L1 [mm]                       | 19.2                |
| L2 [mm]                       | 19.2                |
| Max. delovna temperatura [°C] | 80                  |