

Datum: 26.05.2024

Davčna št.: SI 56119488  
Telefon: 01 500 14 42  
E-mail: [info@podjetje-trg.si](mailto:info@podjetje-trg.si)  
WWW: [www.karcher-trg.si](http://www.karcher-trg.si)



(slika je simbolična)

## Vtični T prik. Metallica vrt., R 1/2, cev Ø 12

Kategorija: [Male branch tee, swivel type, conical ET, coated](#)  
Šifra: **108939RIE**

### Kratek opis

Push-in T-fitting »metallica«, rotating, R 1/2 o., for hose exterior Ø 12, Working pressure -0.98 to 16 bar, nickel-plated brass

All parts with a parallel thread are supplied with an FPM O-ring while the conical threads are coated with preCOTE 5 dispersion

### Tehnične Specifikacije

|                               |                                                           |
|-------------------------------|-----------------------------------------------------------|
| Min. delovna temperatura [°C] | -20                                                       |
| Min. delovni tlak [bar]       | -0.98                                                     |
| Material                      | Nickel-plated brass                                       |
| Navoj                         | R 1/2                                                     |
| Priporočena cev               | PA and PU                                                 |
| Rokav                         | Nickel-plated brass                                       |
| Serijska                      | metallica                                                 |
| Vpenjalni obroč               | Male branch tee, swivel type, conical male thread, coated |
| Za cevi O.D. [mm]             | 12                                                        |
| Max. delovni tlak [bar]       | 16                                                        |
| a/f [mm]                      | 22                                                        |
| L2 [mm]                       | 35.5                                                      |
| L1 [mm]                       | 58.0                                                      |
| Max. delovna temperatura [°C] | 150                                                       |