

Datum: 27.05.2024

Davčna št.: SI 56119488
Telefon: 01 500 14 42
E-mail: info@podjetje-trg.si
WWW: www.karcher-trg.si



(slika je simbolična)

Zaklep hid. spojke na obojestransko 1.4305G 1/4 N.N.I.D. 6.3

Kategorija: [Hydraulic coupling, stainless steel 1.4305, female](#)
Šifra: **107704RIE**

Kratek opis

Hydraulic coupling locking on both sides, Stainless steel 1.4305, G 1/4 IT, I.D. 6.3, Operating pressure max. 250 bar
Hydraulic couplings, both sides sealing, for liquid media acc. to ISO 7241, B Series.
Areas of application: machine and plant engineering, manufacturing industry, chemical / pharmaceutical industry, automotive, food technology.

Tehnične Specifikacije

Min. sobna temperatura [°C]	-15
Min. temperatura medija [°C]	-15
Delovni tlak	Referred to medium temp. of 50 °C, static working pressure
Krogla	Stainless steel 1.4401 at 6 bar and $\Delta_p = 0.5$
Merjenje pretoka	bar
Ohišje	Stainless steel 1.4305
Povezava	G 1/4 IT
Rokav	Stainless steel 1.4305
Tesnilo	FKM
Ventil	Stainless steel 1.4305
Vzmet	Stainless steel 1.4310
DN	6.3
a/f [mm]	19
Dolžina [mm]	57.6
Max. sobna temperatura [°C]	200
Max. temperatura medija [°C]	200
Max. obratovalni tlak [bar]	250
Volumski pretok (zrak) [l/min]	840